















## SPECIFICATIONS

	<b>GEOLOGY</b>	Mica-Schist Quartz (Quartzitic Sandstone)
	<b>TYPE</b>	
	<b>PATTERN</b>	2:1 or 2:3, Sawn Course Heights   Dimensional   Tight-fit
	<b>HEIGHTS</b>	1" - 2" (~50%), 3" (~25%), 5" (~25%)
	<b>LENGTHS</b>	4" - 14"
	<b>DEPTHS</b>	3/4" to 1-1/4"
	<b>COLORS</b>	Gray-Grey , Silver
	<b>COVERAGE</b>	Available in thin veneer only.
	<b>WEIGHT</b>	12.7 lbs. per square foot
	<b>FLATS</b>	5 s/f Bag, 10 s/f Box, 90/150/180 s/f Crate
	<b>CORNERS</b>	5 l/f Bag, 10 l/f Box, 90/100 l/f Crate
	<b>NOTES</b>	Packaged assuming a tight-fit installation comprising of 50% <b>Silver Ledgestone</b> , 50% sawn-height jumpers.   Please review the <b>Corners Installation</b> PDF document.

### ASTM C-97

Water Absorption %	.31 psi
Bulk Specific Gravity	2.83 psi

### ASTM C-170

Parallel to Rift, Dry	36100 psi
Parallel to Rift, Wet	32000 psi
Perpendicular to Rift, Dry	35800 psi
Perpendicular to Rift, Wet	30000 psi

### ASTM C-99

Parallel to Rift, Dry	3770 psi
Parallel to Rift, Wet	3500 psi

### ASTM C-880

Perpendicular to Rift, Dry	1780 psi
Perpendicular to Rift, Wet	1730 psi



**GOLD QUARRY**  
 ANSI/NSC 373-2013  
 C0290908-101



**GOLD FABRICATOR**  
 ANSI/NSC 373-2013  
 C0289215-101