



SPECIFICATIONS

	GEOLOGY	Naturally irregular bedface pieces from the quarry
	TYPE	100% Bedface
	PATTERN	Mosaic
	HEIGHTS	Irregular up to 16" across (Full Bed & Thin Veneer)
	LENGTHS	Random, up to 16"
	DEPTHS	3/4" - 1 1/4" (Thin Veneer); 3"-5" Full Veneer)
	COLORS	Light and warm medium grays.
	COVERAGE	Full Bed Depth Veneer: 30-40 Square Feet Per Ton
	WEIGHT	13.4 lbs. per square foot (Thin Veneer)
	FLATS	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet
	CORNERS	10 l/f Box, 100 l/f Crate, 100 l/f Pallet
	NOTES	

ASTM C-97

Water Absorption %	.31 psi
Bulk Specific Gravity	2.83 psi

ASTM C-170

Parallel to Rift, Dry	36100 psi
Parallel to Rift, Wet	32000 psi
Perpendicular to Rift, Dry	35800 psi
Perpendicular to Rift, Wet	30000 psi

ASTM C-99

Parallel to Rift, Dry	3770 psi
Parallel to Rift, Wet	3500 psi

ASTM C-880

Perpendicular to Rift, Dry	1780 psi
Perpendicular to Rift, Wet	1730 psi

