



SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	100% Bedface
	PATTERN	Natural Course Heights 2:1 Random Ashlar
	HEIGHTS	4" - 12" (Full Bed & Thin Veneer)
	LENGTHS	8"-30" (Full Bed), 8"-24" (Thin Veneer, crated/palletized material can exceed 20")
	DEPTHS	3/4" to 1-1/4" (Thin Veneer); 3" - 5" (Full Bed-Depth)
	COLORS	Grays, blue hues, some buff
	COVERAGE	Full Bed Depth Veneer: 35-40 Square Feet/Ton; also available in thin veneer.
	WEIGHT	14.2 pounds per Square Foot
	FLATS	Thin Veneer: 10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet
	CORNERS	Thin Veneer: 10 Ln/ft Box; 100 Ln/ft Crate; 100 Ln/ft pallet
	NOTES	

ASTM C-97

Water Absorption %	.50 psi
Bulk Specific Gravity	2.79 psi

ASTM C-170

Parallel to Rift, Dry	21300 psi
Parallel to Rift, Wet	20300 psi
Perpendicular to Rift, Dry	29400 psi
Perpendicular to Rift, Wet	29100 psi

ASTM C-99

Parallel to Rift, Dry	2040 psi
Parallel to Rift, Wet	1690 psi

ASTM C-880

Perpendicular to Rift, Dry	
Perpendicular to Rift, Wet	

