















SPECIFICATIONS

	GEOLOGY	Sandstone
	TYPE	100% Bedface
	PATTERN	2:1 Natural Coursed Ashlar or Random Ashlar
	HEIGHTS	2.25 inches, 5 inches, 7.75 inches
	LENGTHS	6 inches - 18 inches
	DEPTHS	3/4 inch - 1.25" inches
	COLORS	Light to medium grays
	COVERAGE	(not available in full bed-depth)
	WEIGHT	12 lbs per square foot
	FLATS	10 sq ft per Box 100 sq ft Crate 180 sq ft Crate
	CORNERS	10 In ft per Box 100 In ft per Crate
	NOTES	*NEW* Light to medium gray tumbled sandstone, with dimensionally sawn heights, packaged assuming a 1/2 inch mortar joint. Available in THIN VENEER Only.

ASTM C-97

Water Absorption %	.12 psi
Bulk Specific Gravity	2.78 psi

ASTM C-170

Parallel to Rift, Dry	14214 psi
Parallel to Rift, Wet	14213 psi
Perpendicular to Rift, Dry	21814 psi
Perpendicular to Rift, Wet	21320 psi

ASTM C-99

Parallel to Rift, Dry	3046 psi
Parallel to Rift, Wet	3191 psi

ASTM C-880

Perpendicular to Rift, Dry	4351 psi
Perpendicular to Rift, Wet	4351 psi

